


2915. TRILLINGSDEMPER MET TAILLE TYPE 1

Afwijkende diameter, hoogte, shore hardheid of draad op aanvraag leverbaar.

Standaard ook in RVS (A2 / A4) leverbaar.

Ook leverbaar in diverse andere materialen zie volgende link [materiaalspecificaties](#)



Artikelcode	D	d	H	G	Lengte	G	Lengte
2915.01000803006.045	10	4,5	8	M 3	6	M3	6
2915.01000804010.045	10	4,5	8	M 3	6	M3	6
2915.01001004010.080	10	8	10	M 4	10	M 4	10
2915.01501504010.085	15	8,5	15	M 4	10	M 4	10
2915.01501504010.120	15	12	15	M 4	10	M 4	10
2915.02001504010.140	20	14	15	M 4	10	M 4	10
2915.02001504011.145	20	14	15	M 4	10	M 4	10
2915.02001906010.145	20	14	19	M 6	18	M 6	18
2915.02001906018.140	20	14	19	M 6	18	M 6	18
2915.02003004010.140	20	14	30	M 4	10	M 4	10
2915.02003006018.120	20	12	30	M 6	18	M 6	18
2915.02502006015.185	25	18	20	M 6	15	M 6	15
2915.02502006015.18A	25	18	20	M 6	15	M 6	15
2915.02502008023.180	25	18	20	M 8	23	M 8	23
2915.03001808023.250	30	25	18	M 8	23	M 8	23
2915.03002008023.220	30	22	20	M 8	23	M 8	23
2915.03002008023.250	30	25	20	M 8	23	M 8	23
2915.03002506015.180	30	18	25	M 6	15	M 6	15
2915.04003008023.250	40	25	30	M 8	23	M 8	23
2915.04003008023.330	40	33	30	M 8	23	M 8	23
2915.04004808023.200	40	20	48	M 8	23	M 8	23
2915.04602510028.400	46	40	25	M10	28	M10	28

Artikelcode	D	d	H	G	Lengte	G	Lengte
2915.05003010028.420	50	42	30	M10	28	M10	28
2915.05504508028.440	55	44	45	M 8	28	M 8	28
2915.05704410028.450	57	45	44	M10	28	M10	28
2915.05704508020.250	57	25	45	M 8	20	M 8	20
2915.05704508020.255	57	25	45	M 8	20	M 8	20
2915.05704510028.440	57	44	45	M10	28	M10	28
2915.06006010028.490	60	49	60	M10	28	M10	28
2915.07005312028.450	70	45	53	M12	28	M12	28
2915.09507516041.800	95	80	75	M16	41	M16	41